

# PALLISIDE

the **smart choice** in weatherboards

## QUALITY GUARANTEED PALLISIDE CONSUMER GUARANTEE

### PRODUCT INFORMATION

- Palliside is suitable as an exterior/interior cladding for horizontal or vertical application subject to the current **Palliside Installation and Technical Guide**.
- If Palliside is to be used in any applications not covered by the current Installation and Technical Guide, written confirmation of suitability should be obtained from Dynex Extrusions Limited prior to the commencement of the project.
- Over time there will be fading and chalking of colours as is customary with all exterior pigmented finishes. This will not affect the long-term durability and weather protection of Palliside. Chalking can be removed by periodic washing with warm soapy water.

### GUARANTEE

- Subject to the above product information, if Palliside is used and installed according to Dynex Extrusions Limited's published recommendations, we guarantee Palliside to be free from defects in material and workmanship for a period of 25-Years from the date of purchase.
- If you consider that our guarantee has not been fulfilled, do not attempt repairs or replacement but contact in the first instance the installer or alternatively Dynex Extrusions Limited P O Box 19-133, Avondale, Auckland. Dynex Extrusions Limited will then recommend appropriate course of action.
- If Palliside has been used and installed in accordance with the requirements of this guarantee (set out above) but does not comply with that guarantee, we will replace the product or refund its purchase price.
- This guarantee is given to consumers as defined in and who have the rights under the Consumer Guarantees Act 1993 and should be read with the statutory consumer guarantees contained in that Act.

**Principal:** Gary and Leslee Porteous

**Project:**

**Address of Installation:** 6 Melandra Road Stanmore Bay

**Date of Installation:** 21<sup>st</sup> October 2009

**Product Installed by:** Tony Hodge of PCS Ltd (Auckland)

# Xternal Solutions Ltd

Po Box 300876 Albany Auckland 0752  
Mobile 027 476 7051 /Fax 09 478 1563

30<sup>th</sup> September 2009

Company:  
From: Tony Hodge

## **4.1 Maintenance and Cleaning**

The appearance of Palliside like other exterior finishes is best maintained by periodic cleaning, especially to the south side of the home and areas that do not receive as much sun light. Any build-up of residue, mould or dirt can be removed easily by soapy water or the use of a sprayed on hypochlorite cleaner such as '30 Seconds' followed by washing down with water.

Avoid using abrasive cleaners, which may have a tendency to cause a dulling of the surface of the Palliside finish. Note Cleaning with thinners, petrol or solvents should be avoided.

All areas where flashings, sealants and penetrations occur should be checked regularly to ensure that their integrity is intact. If any deterioration has taken place, sealants should be reapplied or further action taken if required. Checking such areas should form part of a regular maintenance check, which should also include clearing of spouting and blocked pipes.